

PENTAERYTHRITOL

Application

The product is used in production of paint-and-varnish products, graphic printing paints, lubrication oils, pentaplasts, for nitration and other purposes.

Packaging

Multiwall paper and bitumen-impregnated or laminated bags net weight 25kg; Plastic bags net weight 25kg; PP bags with plastic liner net weight 25kg; Big bags net weight 500 – 1000kg.

Transportation and storage

The product is transported by all modes of transport in accordance with the rules of goods carriage, valid for this mode of transport. The product packed in bags is transported in closed transport facilities. The product packed in big bags is transported both in closed transport facilities and open transport facilities with additional protection from direct sunlight. The product is stored in closed well ventilated warehouses protecting the product from atmospheric precipitates, on pallets at the height of no less than 5 cm from the floor and at a distance of no less than 1 m from the heating units. The product is allowed to store packed in containers at open area under cover or without it, with additional protection from direct sunlight of no less than 5 cm from the ground.

Manufacturer's guaranty

Guaranty period of storage to be 2 years from the manufacturing date, provided that all transportation and shipment rules are observed.

Sales in the Russian Federation and CIS Maxim Zagrebin E-mail: <u>manager@metafrat.ru</u> Phone: +7(984) 000 19 88



Sales for export Pavel Pirogov E-mail: <u>info@metafrat.ru</u> Phone: +7(984) 000 10 55

Main physical and chemical features

Norm		
A		В
High grade	First grade	
White crystal powder		
98,0	95,0	98,7
258	245	259
0,1	0,2	0,1
0,0015	0,01	0,0015
100	200	100
49,7 – 50,0	49,4 - 50,0	49,8 – 50,0
7	no norm	3
5,0 – 7,0	5,0 – 7,0	5,0 – 7,0
	A High grade White crystal p 98,0 258 0,1 0,0015 100 49,7 - 50,0 7	A High grade First grade White crystal powder 98,0 95,0 258 245 0,1 0,2 0,0015 0,01 100 200 49,7 - 50,0 49,4 - 50,0 7 no norm